



- [Home](#)
- [Products](#)
- [Engineering](#)
- [Support](#)
- [Emissions](#)
- [Company Information](#)

Products

Engines

Engines

- [Kubota Super Mini Series](#)
- [Kubota 05 Series](#)
 - [D1005-E3B \(3000rpm\)](#)
 - [D1005-E3B \(3600rpm\)](#)
 - [D1105-E3B \(3000rpm\)](#)
 - [D1305-E3B](#)
 - [D1105-T-E3B](#)
 - [V1505-E3B \(3000rpm\)](#)
 - [V1505-T-E3B](#)
- [Kubota 03-M Series](#)
- [Kubota 07 Series](#)
- [Kubota V3 Series](#)
- [Kubota BG Series \(For Generator\)](#)
- [Kubota WG Series](#)
- [Kubota DF Series](#)
- [Kubota DG Series](#)
- [Kubota EA Series](#)
- [Kubota OC Series](#)
- [Serial Number Identification](#)
- [Model Name Identification](#)

Generators

Parts

Kubota 05 Series V1505-E3B

Model	V1505-E3B	
Emission Regulation	Interim Tier4 /Stage IIIA	
Type	Vertical 4-cycle liquid cooled Diesel	
Number of Cylinders	4	
Bore	mm(in)	78.0(3.07)
Stroke	mm(in)	78.4(3.09)
Displacement	L (cu.in)	1.498(91.41)
Combustion System	IDI	
Intake System	Naturally Aspirated	
Maximum Speed	rpm	3000
	kW	26.2
Output: Gross Intermittent	hp	35.1
	ps	35.6
Direction of Rotation	Counterclockwise Viewed on Flywheel	
Oil Pan Capacity	L(gal)	6.0(1.59)
Starter Capacity	V-kW	12-1.2[US]/12-1.4[EU]
Alternator Capacity	V-A	12-40
Length	mm (in)	591.3(23.28)
Width	mm (in)	396.0(15.59)
Height(1)	mm (in)	607.0(23.90)
Height(2)	mm (in)	232.6(9.16)
Dry Weight	kg (lb)	110.0(242.5)

*Specification is subject to change without notice.

*Output: Gross Intermittent SAE J1995

*Dry weight is according to Kubota's standard specification.
When specification varies, the weight will vary accordingly.

Please note: Click right icon to download plug-in to browse for the first time.



[Product Specifications](#) (PDF 255KB)