

Chapter 4: Parameters

Chapter	Configuration	Content
4	0	
4	0	0
4	0	1
4	0	2
4	0	3
4	0	4
4	2	
4	2	0
4	2	1
4	2	2
4	2	3
4	2	4
4	3	
4	3	0
4	3	1
4	3	2
4	3	3
4	3	4
4	4	
4	4	1
4	6	
4	6	1
4	6	2
4	6	3
4	7	
4	7	0
4	7	1
4	7	2
4	7	3

4	8	
4	8	0
4	8	1
4	8	2
4	8	3
4	9	
4	9	0
4	9	1
4	9	2
4	9	3
4	9	4
4	9	5
4	9	6
4	9	7
4	9	8
4	9	9
4	A	
4	A	0
4	A	1
4	A	2
4	A	3
4	A	4
4	C	
4	C	0
4	C	1
4	D	
4	D	5
4	D	6
4	D	7
4	D	8
4	D	9
4	D	A
4	E	
4	E	5
4	E	6
4	E	7
4	E	8

4	E	9
4	E	A

Description	B400R
Suction Turbine Stop Delay	
none	x
5 seconds	x
10 seconds	x
15 seconds	d
20 seconds	x
Brush Delay (after machine stop)	
0,2 seconds	x
0,5 seconds	x
0,7 seconds	x
1,0 seconds	d
1,5 seconds	x
Silence Mode Suction Turbine Speed	
90%	x
80%	x
70%	x
75%	d
60%	x
e-fuse lifting element	
7 A	d
increased brush pressure stages	
no additional stage	x
one additional stages	x
two additional stages	d
Shaker motor switch on time	
0.6 second	d
1.2 seconds	x
1.8 seconds	x
2.4 seconds	x

Shaker motor switch off time	
0.6 second	x
1.2 seconds	d
1.8 seconds	x
2.4 seconds	x
intervals shaker motor	
1 Intervall	x
2 Intervalls	x
3 Intervalls	x
4 Intervalls	x
5 Intervalls	x
6 Intervalls	x
7 Intervalls	d
8 Intervalls	x
9 Intervalls	x
10 Intervalls	x
Squeegee lifting after	
2.0 Seconds	x
3.0 Seconds	x
4.0 Seconds	d
5.0 Seconds	x
6.0 Seconds	x
Service Alert	
Service alert not installed	x
Service alert installed	d
Speed Transport ride	
50%	x
60%	x
70%	x
80%	x
90%	x
100%	d
Speed Cleaning ride	
50%	x
60%	x
70%	x
80%	x

90%	x
100%	d